



>>Home >>Whisperwatt Generators

Product Broc
Operations M
Technical L

All Whisperwatt Single/Three phase models

DCA-25SSIU

DCA-45SSIU2

DCA-70SSJU2

DCA-100SSVU

DCA-150SSVU

DCA-220SSVU

DCA-300SSK3

DCA-400SSK3

DCA-400SSV

DCA-600SSK

DCA-800SSK

DCA-25SSIU

The WhisperWatt line of portable generators has thrived with a revolving field, self-ventilated, drip-proof, single bearing design.

The DCA-25SSIU sports 27kVA/22kW standby output and 25kVA/20kW prime output. The generator is powered by a 4-cylinder, 31-horsepower Isuzu C240 diesel engine and the unit controls voltage regulation to +/-1 percent no load to full load. Sound level is an impressive 65dB(A) full load at 23 feet while the generator has a 17-gallon (65 liters) fuel tank.



Performance Data

Standby Output	22 kW , 27 kVA
Prime Output	20 kW , 25 kVA
Generator RPM	1800 RPMs
Generator Design	Revolving Field Self-Ventilated Dip-Proof Single Bearing
Voltage Regulation - (No Load to Full Load)	1 %
Power Factor	0.8
Armature Connection	Star with Neutral / Zigzag
Excitation	Brushless with AVR
No. Poles	4 Pole
Frequency	60 Hz
Available Voltages - 3 Phase	208, 220, 240, 416, 440, 460, 480V Switchable Volts
Available Voltages - Single Phase	120, 127, 139, 240, 254, 277 Switchable Volts
Amps - Single Phase 120V	55.5 (4 Wire) 60x2(Zigzag) Amps
Amps - Single Phase 240V	27.8 (4 Wire) 60 (Zigzag) Amps
Amps - Three Phase 240V	60 Amps
Amps - Three Phase 480V	30 Amps
Insulation	Class F
Sound Level dB(A) - Full Load at 23 feet	67 dB(A)
Power Source	
Engine Make / Model	Isuzu C240
Dimensions	
Overall Length	77 in. , 195 cm
Overall Width	30 in. , 75 cm
Overall Height	39 in. , 100 cm
Approx. Net Wt. Dry	1543 lbs. , 700 kg.

Please note, product information is not up-to-date while we work on our new website. Please confirm all products and specifications with our sales department. Sorry for the inconvenience!