



>>Home >>Whisperwatt Generators

All Whisperwatt Single/Three phase models

-DCA-25SSIU
-DCA-45SSIU2
-DCA-70SSJU2
-DCA-100SSVU
-DCA-150SSVU
-DCA-220SSVU
-DCA-300SSK3
-DCA-400SSK3
-DCA-400SSV
-DCA-600SSK
-DCA-800SSK

DCA-45SSIU2

The WhisperWatt line is known for excellent voltage regulation and each model continues to meet customer needs.

MQ Power's DCA-45SSIU2 controls power within +/-1 percent of mean voltage. The unit generates 47kVA/37kW standby output and 45kVA/36kW prime output. Standard features include a complete power panel, automatic safety shutdown system, brushless generator design, easy maintenance design with direct access to all filters, and an internal fuel tank.



Performance Data

Standby Output	37 kW , 47 kVA
Prime Output	36 kW , 45 kVA
Generator RPM	1800 RPMs
Generator Design	Revolving Field Self-Ventilated Dip-Proof Single Bearing
Voltage Regulation - (No Load to Full Load)	1.5 %
Power Factor	0.8
Armature Connection	Star with Neutral / Zigzag
Excitation	Brushless with AVR
No. Poles	4 Pole
Frequency	60 Hz
Available Voltages - 3 Phase	208, 220, 240, 416, 440, 460, 480V Switchable Volts
Available Voltages - Single Phase	120, 127, 139, 240, 254, 277 Switchable Volts
Amps - Single Phase 120V	100 (4 Wire) 108x2 (Zigzag) Amps
Amps - Single Phase 240V	50 (4 Wire) 108 (Zigzag) Amps
Amps - Three Phase 240V	108 Amps
Amps - Three Phase 480V	54 Amps
Insulation	Class F
Sound Level dB(A) - Full Load at 23 feet	66 dB(A)
Power Source	
Engine Make / Model	Isuzu 4BG1
Dimensions	
Overall Length	79 in. , 200 cm
Overall Width	35 in. , 90 cm
Overall Height	49 in. , 125 cm
Approx. Net Wt. Dry	2403 lbs. , 1090 kg.

Please note, product information is not up-to-date while we work on our new website.

Please confirm all products and specifications with our sales department. Sorry for the inconvenience!